

Circular Counter

Item.no IS-9496

Complete with:

4 posts, 2 corner trims, 1 top shelf,
1 bottom shelf, 1 inner shelf
4 feet and 1 carrying bag



1

Screw in the 4 adjustable feet.



2



Attach the four posts and lock the bottom clamps.

3

Add the inner shelf.



4



Attach the table top and lock the top clamps

5



Mount the graphic panel.

6




Ready to go!

Graphic production

Closed panel




1 section open panel



Graphic panel attachments

Accessories

Magnetic tape (not incl.)
12 mm/0.5" A tape, 30 m / 98 ft. DM-013-AC
Each panel needs 6 m/20 ft. (in the midi size)



Printer material

We recommend the following material:

Poster paper: 180 gr / 0.4 lb.

The printed graphic panels must be laminated before use.
Front side: 125 microns (0,125 mm) / 0.005" "deep crystal"
Reverse side: 250 microns (0,250 mm) /0.010" "stop light"

Polyester film: 330-370 microns (0,350 mm) / 0.013-0.015"
Top laminate: 125 microns (0,125 mm) / 0.005" "deep crystal"

Mounting of Magnetic Tape

Magnetic tape to be fixed vertically along each side of the graphic panels.

IMPORTANT Carefully mount the magnetic tape slightly inset from the edge of the graphic panel by approximately 0,25 mm / 0.010". Once mounted, a very thin straight white line should show between the edge of the graphic and the outside edge of the magnetic tape. Do not exceed 0,5 mm / 0.020".

Application Techniques

To obtain optimum adhesion, the bonding surfaces must be well unified, clean and dry. Typical surface cleaning solvents are isopropyl alcohol/water mixture (rubbing alcohol) or heptane.

Note: Be sure to follow solvent manufacturer's precautions and directions for use when using solvents.